

EN 420:2003+A1:2009

EN 388:2016

EN 407:2004

PPE CATEGORY II



Read the instructions carefully.

Complies with the requirements of the Regulation (EU) 2016/425

Product: Protective knitted sleeve.

Design:	„CIRU“	Code:	3630 110 038 XX	Size:	35 – length 35 cm, 45 - length 45 cm
Material:	55% Aramid (Para Aramid), 25% Mod acrylic, 20% Glass.				

Purpose: They may serve as a protection of hands, especially against cutting, against dirt and protection in the working areas where workers have to face mechanical hazards (abrasions, cuts ...), for example in automotive and engineering industry. The sleeve is resistant to contact heat to 100 °C for 35 seconds. Use the sleeves on clean and dry hands.

Levels of performance are based upon the results of laboratory tests, which do not necessarily reflect actual conditions in the workplace. The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified below. (The higher the number, the higher the protection factor).

EN 388:2016	A (0-4)	Abrasion resistance:	Performance level 2	 A.B.C.D.E.F.	The protective properties work only in the area of arm covered by the main material of the muff and against the above specified risks. Do not use as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). Based on observance of the prescribed maintenance the stability of required properties essential for assessment of compliance with the above specified technical standards is guaranteed, not more than 5 washing cycles.
	B (0-5)	Blade cut resistance (coupe test)	Performance level 5		
	C (0-4)	Tear resistance	Performance level 4		
	D (0-4)	Puncture resistance	Performance level 4		
	E (A-F)	Cut Resistance (TDM)	Performance level F		
	F(P/X nebo nic)	Impact protection	Performance level X		
EN 407:2004	A (0-4)	Burning resistance	Performance level X	 A.B.C.D.E.F.	
	B (0-4)	Contact heat resistance	Performance level 1		
	C (0-4)	Convecting heat resistance	Performance level X		
	D (0-4)	Radiant heat resistance	Performance level X		
	E (0-4)	Resist. to small splashes of molten metal	Performance level X		
	F (0-4)	Resist. to large splashes of molten metal	Performance level X		
EN 420 - protective gloves (general requirements)					
	(1-5)	Dexterity	Performance level X		
„X“ = test not performed or not applicable.					

Please note: Any user should carry out examination of each sleeves before and after their use for the purpose of assurance of the required quality. Do not use any damaged sleeves. Do not use the sleeves for handling of flames, chemicals or greasy objects. The sleeves must be used with gloves showing at least the same level of protection. Not resistant to soaking. It is not allowed to wear these sleeves in cases with risk of entanglement with moving parts of machines. For dulling during the cut resistance test (B), the coupe test results are only indicative while the TDM cut resistance test (E) is the reference performance result. The sleeves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective sleeves. It is the responsibility of every user to judge, whether the sleeve is used in suitable conditions.

Maintenance, lifetime: After use, make sure that all contaminating substances are removed from the sleeves. Thus, you can extend its lifespan. It is sleeves meant for short-time use only. Dry a damp sleeve further away from sources of heat at the room temperature. Washing as a synthetic material with max. temperature of 40 °C, not more than 5 washing cycles, or any dirt shall be brushed away from a muff using a soft brush. Do not use BIO laundry detergents and agents that contain optical highlighters; considerate handling; rinsing in cold water; short spinning; no bleaching; no tumble drying; no ironing; no chemical cleaning. Worn through, burned through, strongly fouled or stiffened sleeves have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 5 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: The product does not contain any substances, which are known for their adverse impact on hygiene and health of users nor there are suspected of it. In spite of that, the materials which come into contact with a user's skin can cause an allergic reaction in sensitive individuals. If skin irritation or allergic reaction contact, do not use sleeves and seek medical advice.

Disposal: Dispose of used sleeves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused sleeves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0120, SGS United Kingdom Ltd. Unit 202b, Worle Parkway, Weston-super-Mare, BS22 6WA, UK.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking (sample) - description:			
CIRU	Type		Symbol indicating the necessity to read the instructions
45	Length	„EL“	Identification production
 EN388	 EN407	Pictogram and number of the standard that the product complies with	 Manufacturer identification
2544F	X1XXXX	Results of the tests carried out	 XX/XXXX Use by (month/year)
	Conformity mark	ZA/XXXX/XXX CAT II	Lot – mark/year of production/order number Glove Category

If you need more information, please contact manufacturer:



Poděbradská 260/59, Hloubětín, 198 00 Praha 9, Czech Republic.